

USER MANUAL & WARRANTY GUIDE

HOW TO USE:

- 1 PULL BOTTOM CAR TO REVEAL
- HIDDEN COMPARTMENT
- 2 SCREW IN 510 THREAD CARTRIDGE 3 - SNAP BACK INTO PLACE VIA MAGNETIC LOCK
- 4 PUFF 3 TIMES WITHIN 1.5 SECONDS TO CHANGE VOLTAGE (GREEN LIGHT = LOW 3.0 VOLTAGE, RED LIGHT = HIGH 3.8 VOLTAGE)

SCAN TO SEE
THE WARRANTY
POLICY

IMPORTANT SAFETY INFORMATION:

- 1 INTERNAL PARTS OF THE DEVICE REACH HIGH TEMPERATURES.
 2 DO NOT DISMANTI E REYOND CLEANING AND MAINTENANCE.
- DOING SO WILL VOID THE WARRANTY

STORAGE

- 1 STORE THE DEVICE AT LOW TEMPERATURE (BELOW 68° FAHRENHEIT IS RECOMMENDED), LOW HUMIDITY, NO DUST AND NO CORROSIVE
- GAS ATMOSPHERE.

 2 KEEP THE DEVICE AWAY FROM CHILDREN AND PETS TO AVOID ANY ACCIDENTS.

